

This is a list of the standard range of scissor lift tables. There is flexibility on the size of platform on the majority of the scissor tables listed. We can fit a wide range of accessories to the scissor tables e.g guard rails, gates, bridging flaps, safety curtains, ball tables etc. Ring us to discuss your exact requirements.
We can also offer a extensive customising service for special applications and requirements.

SINGLE SCISSORS

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JX0-5/50-1C	500	800 x 600	800 x 600	500	180	9	0.75	130
JX1-5/90-1C	500	1350 x 800	1350 x 790	900	180	20	0.75	210
JX1-5/90-1C	500	1350 x 1000	1350 x 790	900	180	20	0.75	220
JX1-5/125-1C	500	1800 x 800	1800 x 790	1250	220	19	0.75	255
JX2-5/160-1C	500	2250 x 800	2250 x 790	1600	220	33	0.75	430
JX1-10/55-1C #	1000	1000 x 800	1000 x 790	550	180	12	0.75	185
JX1-10/90-1C	1000	1350 x 800	1350 x 790	900	180	20	0.75	210
JX1-10/90-1C	1000	1350 x 1000	1350 x 790	900	180	20	0.75	220
JX1-10/125-1C	1000	1800 x 800	1800 x 790	1250	220	33	0.75	255
JX2-10/125-2C	1000	1800 x 1200	1800 x 990	1250	235	27	1.1	410
JX2-10/160-2C	1000	2250 x 1000	2250 x 990	1600	235	28	1.1	465
JX2-10/160-2C	1000	2250 x 1500	2250 x 1290	1600	300	28	1.1	545
JX2-20/90-2C	2000	1350 x 800	1350 x 790	900	230	26	0.75	295
JX2-20/90-2C	2000	1350 x 1000	1350 x 790	900	230	26	0.75	310
JX2-20/125-2C	2000	1800 x 800	1800 x 790	1250	250	28	1.1	355
JX2-20/125-2C	2000	1800 x 1200	1800 x 990	1250	250	28	1.1	410
JX2,5-20/125-2C	2000	2000 x 1200	2000 x 1090	1250	250	32	1.1	480
JX2,5-20/125-2C	2000	2000 x 1500	2000 x 1290	1250	250	32	1.1	525
JX3-20/160-2C	2000	2250 x 1200	2250 x 960	1600	300	31	2.2	660
JX3-20/160-2C	2000	2250 x 1500	2250 x 1260	1600	300	31	2.2	750
JX2,5-30/90-2C #	3000	1350 x 1000	1350 x 990	900	300	16	2.2	350
JX2,5-30/90-2C	3000	1350 x 1100	1350 x 1090	900	300	17	2.2	360
JX3-30/110-2C	3000	1800 x 1000	1800 x 960	1100	300	20	2.2	540
JX3-30/130-2C	3000	2000 x 1200	2000 x 960	1300	300	25	2.2	595
JX3-30/130-2C	3000	2000 x 1500	2000 x 1260	1300	300	25	2.2	650
JX3-30/160-2C	3000	2250 x 1200	2250 x 960	1600	300	31	2.2	660
JX3-30/160-2C	3000	2250 x 1500	2250 x 1260	1600	300	31	2.2	725
JX3-30/200-2C	3000	3000 x 1200	2800 x 960	2000	300	42	2.2	780
JX3-30/200-2C	3000	3000 x 1500	2800 x 1260	2000	300	42	2.2	860
JX3-40/90-2C #	4000	1500 x 1200	1500 x 960	900	300	17	2.2	490
JX3-40/130-2C	4000	2000 x 1200	2000x960	1300	300	25	2.2	590
JX3-40/130-2C	4000	2000 x 1500	2000x1260	1300	300	25	2.2	660
JX4-40/160-2C	4000	2500 x 1200	2500x960	1600	400	33	2.2	1100
JX4-40/160-2C	4000	2500 x 1500	2500x1260	1600	400	33	2.2	1210
JX4-40/200-2C	4000	3000 x 1200	3000x960	2000	400	32	4.0	1260
JX4-40/200-2C	4000	3000 x 1500	3000x1260	2000	400	32	4.0	1380
JX4-50/130-2C	5000	2250 x 1200	2250x960	1300	400	38	2.2	1030
JX4-50/130-2C	5000	2250 x 1500	2250x1260	1300	400	38	2.2	1130
JX4-50/160-2C	5000	2500 x 1200	2500x960	1600	400	47	2.2	1100
JX4-50/160-2C	5000	2500 x 1500	2500x1260	1600	400	47	2.2	1210
JX4-50/200-2C	5000	3000 x 1200	3000x960	2000	400	32	4.0	1260
JX4-50/200-2C	5000	3000 x 1500	3000x1260	2000	400	32	4.0	1380
JX4-60/130-2C	6000	2250 x 1200	2250x960	1300	400	38	2.2	1020
JX4-60/160-2C	6000	2500 x 1200	2500x960	1600	400	47	2.2	1100
JX5-80/150-2C	8000	3000 x 2000	3000x1800	1500	600	31	4.0	1940
JX5-100/150-4C	10000	3000 x 2000	3000x1800	1500	600	45	4.0	1940

#) Remote power pack

SINGLE SCISSORS ECONOMIC

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JX0-5/80-1C	500	1200 x 800	1160 x 600	800	200	19	0.72	150
JX0-10/80-1C	1000	1200 x 800	1160 x 600	800	200	19	0.72	160
JX0-20/80-1C	2000	1350 x 800	1350 x 600	800	220	25	1.43	210
JXL-10/75-2C	1000	1500 x 900	1440 x 870	750	80	19	0.75	290
JXL-10/75-2CB	1000	1500 x 1100	1440 x 1070	750	80	19	0.75	340
JXU-10/75-2C	1000	1500 x 1100	1440 x 1070	750	80	19	0.75	320

Delivered only in blue colour RAL 5019 and without over limit switch.

VERTICAL DOUBLE SCISSORS

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXY0-4/80-1C	400	800 x 600	700 x 600	800	200	19	0.55	120
JXY2-5/180-1C**	500	1350 x 1000	1350 x 850	1800	350	21	2.2	450
JXY2-5/320-2C	500	2250 x 1000	2250 x 850	3200	400	36	2.2	650
JXY2-10/180-2C	1000	1350 x 1000	1350 x 850	1800	350	21	2.2	450
JXY2-10/200-2C	1000	1500 x 1000	1500 x 850	2000	350	21	2.2	490
JXY2-10/250-2C	1000	1800 x 1000	1800 x 850	2500	350	30	2.2	540
JXY3-10/320-2C	1000	2250 x 1000	2250 x 850	3200	500	43	2.2	870
JXY2-10/330-2C*	1000	1650 x 1200		3300	530	34	2.2	800
JXY2-10/330-2C*	1000	1650 x 1200	1650 x 1000	3300	530	34	2.2	665
JXY2-15/180-2C	1500	1350 x 1000	1350 x 850	1800	400	21	2.2	450
JXY3-20/200-2C	2000	1500 x 1000	1500 x 850	2000	500	25	2.2	645
JXY3-20/200-2C	2000	1500 x 1800	1500 x 1560	2000	500	40	2.2	900
JXY3-20/320-2C	2000	2250 x 1000	2250 x 850	3200	530	40	4.0	870
JXY3-20/380-2C*	2000	2250 x 1200	2250 x 1050	3800	800	41	4.0	1150
JXY3-20/380-2C*	2000	2250 x 1800	2250 x 1560	3800	800	41	4.6	1250
JXY3-20/430-2C	2000	3000 x 1200	3000 x 1050	4300	650	43	4.0	1140
JXY3,5-25/320-2C	2500	2500 x 1200	2500 x 1060	3200	530	40	4.6	1350
JXY4-30/300-2C	3000	2500 x 1300	2250 x 1150	3000	700	33	4.0	1580
JXY4-40/300-2C	4000	2500 x 1500	2250 x 1350	3000	700	46	4.0	1650

* Triple scissors

Remote power packs on all vertical double scissors

All models, except 860660, are with remote power pack

TANDEM SCISSORS

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXX1-10/90-2C	1500	2750x1000	2700 x 790	900	235	18	1.1	500
JXX2-20/90-4C #	2000	2750 x 1000	2700 x 790	900	240	18	2.2	610
JXX2-20/125-4C	2000	3650 x 1000	3600 x 790	1250	260	28	2.2	740
JXX2-20/125-4C	2000	4000 x 2000	3600 x 1760	1250	260	27	2.2	1300
JXX2-20/160-4C	2000	4550 x 1000	4500 x 850	1600	300	29	2.2	890
JXX2-20/160-4C	2000	4550 x 1500	4500 x 1290	1600	300	29	2.2	1080
JXX3-20/200-4C	2000	6000 x 1500	5600 x 1260	2000	300	45	4.6	1800
JXX3-20/200-4C	2000	6000 x 2000	5600 x 1760	2000	300	45	4.6	2150
JXX2-30/90-4C#	3000	2750 x 1000	2700 x 790	900	240	18	2.2	610
JXX2-30/125-4C	3000	3650 X 1000	3600 X 790	1250	260	28	2.2	740
JXX2,5-30/125-4C	3000	4050 x 1200	4000 x 1090	1250	260	28	2.2	890
JXX2,5-30/160-4C	3000	4550 x 1000	4500 x 850	1600	300	41	2.2	900
JXX3-30/200-4C	3000	6000 x 1500	5600 x 1260	2000	300	45	4.6	1800
JXX3-30/200-4C	3000	6000 x 2000	5600 x 1760	2000	300	69	2.2	2270
# Remote Power pack								
JXX3-40/110-4C	4000	3600x1000	3600x960	1100	300	33	2.2	980
JXX3-40/130-4C	4000	4050x1200	4000x960	1300	340	29	4.6	1,100
JXX3-40/160-4C	4000	4550x1200	4500x960	1600	340	34	4.6	1,400
JXX3-40/160-4C	4000	4550x2000	4500x1760	1600	340	34	4.6	1,600
JXX3-40/200-4C	4000	6000x1500	5600x1260	2000	340	45	4.6	1,800
JXX3-40/200-4C	4000	6000x2000	5600x1760	2000	340	45	4.6	2,270
JXX3-50/110-4C	5000	3600x1000	3600x960	1100	300	33	2.2	980
JXX3-50/130-4C	5000	4050x1200	4000x960	1300	340	29	4.6	1,100
JXX3-50/160-4C	5000	4550x1200	4500x960	1600	340	34	4.6	1,300
JXX3,5-50/160-4C	5000	4550x2000	4500x1760	1600	340	34	4.6	1,600
JXX3,5-50/200-4C	5000	6000x1500	5600x1260	2000	340	45	4.6	1,800
JXX3,5-50/200-4C	5000	6000x2000	6000x1760	2000	400	57	4.6	2,700
JXX3,5-60/110-4C	6000	3650x1200	3600x960	1100	340	23	4.6	1,200
JXX3,5-60/130-4C	6000	4050x1200	4000x960	1300	340	29	4.6	1,250
JXX3,5-60/160-4C	6000	4550x1200	4500x960	1600	340	34	4.6	1,300
JXX3,5-60/160-4C	6000	4550x2000	4500x1760	1600	340	34	4.6	1,600
JXX4-60/200-4C	6000	6050x1500	6000x1260	2000	400	45	4.6	2,340
JXX4-60/200-4C	6000	6050x2000	6000x1760	2000	400	57	4.6	2,700
JXX4-80/130-4C	8000	4550x1200	4500x960	1300	400	43	4.6	1,680
JXX4-80/160-4C	8000	5050x1200	5000x960	1600	400	52	4.6	1,800
JXX4-80/160-4C	8000	5050x2000	5000x1760	1600	400	52	4.6	2,400
JXX4-80/200-4C	8000	6050x1500	6000x1260	2000	400	68	4.6	2,340
JXX4-80/200-4C	8000	6050x2000	6000x1760	2000	400	68	4.6	2,700

LOADING DOCK TABLES

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JX3-20/130-2CK	2000	2000x1500	2000x1260	1300	305	26	2.2	950
JX3-20/130-2CK	2000	2000x2000	2000x1760	1300	305	26	2.2	1100
JX3-20/160-2CK	2000	2500x1500	2250x1260	1600	305	31	2.2	1000
JX3-20/160-2CK	2000	2500x2000	2250x1760	1600	305	31	2.2	1170
JX3-20/160-2CK	2000	2500x2400	2250x2160	1600	305	31	2.2	1320
JX3-20/160-2CK	2000	3000x2000	2500x1760	1600	305	33	2.2	1300
JX3-20/160-2CK	2000	3000x2400	2500x2160	1600	305	33	2.2	1575

JX3-30/130-2CK	3000	2000x1500	2000x1260	1300	305	26	2.2	950
JX3-30/130-2CK	3000	2000x2000	2000x1760	1300	305	26	2.2	1100
JX3-30/160-2CK	3000	2500x1500	2250x1260	1600	305	33	2.2	1000
JX3-30/160-2CK	3000	2500x2000	2250x1760	1600	305	33	2.2	1170
JX3-30/160-2CK	3000	2500x2400	2250x2160	1600	305	33	2.2	1320
JX3,5-30/160-2CK	3000	3000x2000	2500x1760	1600	305	33	2.2	1330
JX3,5-30/160-2CK	3000	3000x2400	2500x2160	1600	305	33	2.2	1600

JX3,5-40/130-2CK	4000	2000x1500	2000x1260	1300	305	26	2.2	1000
JX3,5-40/130-2CK	4000	2000x2000	2000x1760	1300	305	26	2.2	1150
JX4-40/160-2CK	4000	2500x1500	2500x1260	1600	450	34	2.2	1300
JX4-40/160-2CK	4000	2500x2000	2500x1760	1600	450	34	2.2	1500
JX4-40/160-2CK	4000	2500x2400	2500x2160	1600	450	34	2.2	1700
JX4-40/160-2CK	4000	3000x2000	2500x1760	1600	450	26	4.6	1650
JX4-40/160-2CK	4000	3000x2400	2500x2160	1600	450	26	4.6	1830

JX4-60/130-2CK	6000	2250x1500	2250x1260	1300	420	27	4.6	1300
JX4-60/130-2CK	6000	2250x2000	2250x1760	1300	420	27	4.6	1500
JX4,5-60/160-2CK	6000	2500x1500	2500x1260	1600	450	34	4.6	1390
JX4,5-60/160-2CK	6000	2500x2000	2500x1760	1600	450	26	4.6	1600
JX4,5-60/160-2CK	6000	2500x2400	2500x2160	1600	450	26	4.6	1800
JX4,5-60/160-2CK	6000	3000 x 2000	2500x1760	1600	450	33	4.6	1750
JX4,5-60/160-2CK	6000	3000 x 2400	2500x2160	1600	450	33	4.6	1930

JX5-80/160-2CK	8000	3000 x 2000	3000x1760	1600	600	33	4.6	3200
JX5-80/160-2CK	8000	3000 x 2400	3000x2160	1600	600	33	4.6	3400

JX5-100/160-4CK	10000	3000 x 2000	3000x1760	1600	650	48	4.6	3400
JX5-100/160-4CK	10000	3000 x 2400	3000x2160	1600	650	48	4.0	3600

The loading dock tables are as standard equipped with following:

8 mm steel plate ON platform instead of 5 mm as the standard table

Oil filled minus side of cylinders

Reinforced platform with more profiles

Service hatch in platform

Mechanical bottom stops

Lifting eyes

Two component paint 120 my

CAR LIFT TABLES

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JX4-20/350-2C	2000	5000x2500	5000x2160	3500	450	54	4.6	2600

JX5-25/400-2C	2500	6000x2500	5700x2150	4000	650	79	4.6	3600
JX5-25/450-2C	2500	6100x2500	6100x2150	4500	650	90	4.6	3600
JX6-25/500-2C	2500	7500x2500	7500x2150	5000	750	65	2x4,6	5100

JXY5-20/500-4C	2000	5000x2500	4500x2150	5000	1200	65	2x4,6	4500
----------------	------	-----------	-----------	------	------	----	-------	------

JXY6-25/600-4C	2500	5000x2500	4500x2150	6000	1400	85	2x4,6	6300
----------------	------	-----------	-----------	------	------	----	-------	------

JXY6-20/700-4C	2000	5700x2500	5700x2150	7000	1400	85	2x4,6	7200
----------------	------	-----------	-----------	------	------	----	-------	------

LOW PROFILE & U-SHAPE SCISSORS

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXL-5/80-2C	500	1350 x 600	1283 x 532	800	80	19	0.48	180
JXL-5/80-2C	500	1350 x 800	1283 x 732	800	80	19	0.48	190
JXL-5/80-2C	500	1350 x 1050	1283 x 982	800	80	19	0.48	210
JXL-10/80-2C	1000	1350 x 600	1283x532	800	80	19	0.72	185
JXL-10/80-2C	1000	1350 x 800	1283x732	800	80	19	0.72	200
JXL-10/80-2C	1000	1350 x 1050	1283x982	800	80	19	0.72	220
JXL-20/80-2C	2000	1400 x 800	1300x730	800	95	30	0.72	270
JXL-20/80-2C	2000	1400 x 1200	1300x1180	800	95	30	0.72	300
Ramp for JXL	closed height 80 mm							
Ramp for JXL	closed height 95 mm							
JXU-5/80-2C	500	1350 x 1050	1283x982	800	80	19	0.48	185
JXU-10/80-2C	1000	1350 x 1050	1283x982	800	80	19	0.72	200
JXU-20/80-2C	2000	1400 x 1200	1300x1180	800	95	30	0.72	300
JXU-16/80-2C	1600	1530 x 1670		800	85	15	1.4	580
JXU-16/80-2CB	1600	1530 x 1870		800	85	15	1.4	590

Note ! Remote power pack on all low profile lifts

LOW PROFILE & U-SHAPE IN STAINLESS STEEL.

Description MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXL-8/80-2C	800	1350 x 800	1283 x 732	800	80	19	0.72	200
JXL-8/80-2C	800	1350 x 1050	1283 x 982	800	80	19	0.72	220
JXU-8/80-2C	800	1350 x 1050	1283 x 982	800	80	19	0.72	200

Note ! Remote power pack on all low profile lifts

LOW PROFILE TANDEM SCISSOR TABLES

Description MODEL	Capacity	Platform (L x W)	Base frame (L x W)	Lift stroke	Closed height	Lift time	Motor	Weight
JXXL-012080-2C	1200	2700x850		800	90	17	1.4	450
JXXL-015080-2C	1500	2700x850		800	90	17	1.4	450
JXXL-030080-2C	3000	2800x1100		800	130	28	1.4	650

GOLF BUGGIES & DDA SERVICES BENCH SCISSOR TABLES

Description MODEL	Capacity	Platform (L x W)	Base frame (L x W)	Lift stroke	Closed height	Lift time	Motor	Weight
JXL-10/80-2CG *)	1000	2000 x 1400	1283 x 982	800	80	19	0.72	220
JX1-5/125-2CG	500	2000 x 1500	1800 x 990	1250	220	38	0.75	480
M2-10/125-2CG	1000	2000 x 1500	1800 x 990	1250	235	27	1.1	565
JXL-18/80-2CG *)	1800	2100 x 1500	1300 x 1180	800	95	30	0.72	300

*) Including ramp, remote power pack